

Highlights:

- 2 x XLR inputs & outputs
- Integrated Bluetooth receiver (Version 4.2)
- 4 x 4 channels Dante™ & AES67
- All-in-one mixing & sound processing
- Ultra efficient cooling
- Superior sound quality & low latency

Product information:

The NWP222 is a Dante™/AES67 network input panel, featuring two XLR input and output connectors and an integrated Bluetooth receiver, which can be used to transmit or receive audio signals in a Dante™ audio network. The audio inputs can be switched between line-level and microphone-level audio signals and phantom power (+48 V DC) can be applied to the XLR input connectors for powering condenser microphones. Various further integrated functions such as integrated equalizing, automatic level control and other device settings can be configured through the AUDAC Touch™ app. Besides the elegant design, the front panel is finished with high-quality fingerprint-resistant glass. The wall panels are compatible with EU-style standard or 2-gang US standard in-wall boxes, making the wall panel the ideal solution for solid and hollow walls. Black and white colour options are available to blend into any architectural design. The IP-based communication makes it future-proof while also being backwards compatible with many existing products. In contrast, the limited PoE power consumption makes it compatible with any PoE network-based installation.

Applications:

- Corporate
- Sporting facilities
- Hotels
- Education
- Government facilities
- Bars & Restaurants



Certification:



Properties:



Additional Inputs:



System specifications:

Inputs		2 x XLR female (in)
		2 x XLR male (out)
Control		1 button - Bluetooth discoverable
Indicators		1 LED (RGB) - Bluetooth status
Configurable settings		IP settings
		Device name
		Input range (Mic / Line)
		Gain
		Phantom power
		DSP (EQ)
		Mixing
Configuration		Audac Touch™
Integrated DSP		Yes (EQ)
Automatic level control		Yes
Phantom power		+48 V DC
Power	Supply	PoE powered (IEEE 802.3af)
Connectors		XLR Female (mic in)
		RJ45 (network + PoE)
		2 x XLR female (audio in)
		2 x XLR male (audio out)

Product Features:

Construction	ABS
Front finish	Elegant ABS front panel with glass
Dimensions	160 x 88 mm (W x H) (Remote wall panel)
Colours	White (RAL9003) (DWP240/W)
	Black (RAL9005) (DWP240/B)
Compatible devices	Any Dante™/AES67 compatible audio device
Installation standard	Compatible with EU installation materials
	2-gang US standard (NWP222US)

Variants:

- NWP222/B - Black version - EU-style standard
- NWP222/W - White version - EU-style standard
- NWP222US/B - Black version - 2-gang US standard
- NWP222US/W - White version - 2-gang US standard